

JACKS: (2) RJ11, DB-25 female, Power jack
 DIMENSIONS: 6.125 x 8.5 x 1.625"
 REN: .4a and .7B
 POWER REQ.: 8 Watts (Max.)
 POWER PACK (Provided): IN: 105 to 130 VAC, 60 Hz
 OUT: 10.2 VAC as 780 mA
 FUSE: 5 by 20mm, 2 amp, Fast-blow type recommended
 TRANSMIT SIGNAL LEVEL: -0.5 TO -15.5 dBm
 TRANSMIT FREQUENCY TOLERANCE: +/- 0.01 %
 RECEIVE SIGNAL LEVEL: 0 TO -43 dBm
 RECEIVE FREQUENCY TOLERANCE: +/- 7 Hz

ELECTRICAL SPECIFICATIONS

Ringer Equivalence Number.....0.4A and 0.7B
 Typical power requirements.....+12v < 50 ma
 -12v < 50 ma
 + 5v < 1 amp
 - 5v < 50 ma

PERFORMANCE SPECIFICATIONS

Transmit signal level.....-0.5 to -15.5 dBm
 Transmit frequency tolerance.....±0.01 percent
 Receive signal level.....0 to -43 dBm
 Receive frequency tolerance.....±7 Hz

(dtc-07/30/93)
 (smm 08/26/93)