



SPARCBOOK 3TX specs

Processor	170MHz TurboSPARC
Level 2 Cache	256K
System Performance	3.5 SPECint95, 3.0 SPECfp95
Memory	32, 64 or 128MB DRAM SIMMs; user upgradable
Storage	Removable 1.2GB 2.5" Winchester hard disk
Internal Display	10.4" TFT LCD; displays 800 x 600 resolution and 256 colors from a palette of 262,144
External Display	Supports external monitors and projectors with software-selectable resolutions of up to 1280 x 1024; displays 256 colors from a palette of 16.7 million colors
Video RAM	2MB
Graphics Accelerator	Weitek P9100
Keyboard/Pointing Device	Lexmark 84-key, including built-in numerical keypad; three button pointing stick device Multilingual options including Kanji Supports external U.S. and International Sun Type 4/5 keyboards and mechanical or optical mouse
Modem/Fax	U.S., Canada: internal 14.4 Kbaud V.32bis Rockwell 144ACW Modem (Hayes-compatible) with V.42bis data compression to 57.6 Kbaud Includes send/receive fax for standard Group III fax Supports CCITT V.29, V.27ter, V.22bis, V.22, V.21, Bell 212A, 103 and MNP 1-5 standards RJ11 jack socket; U.S. modem cable included in applicable territories
PCMCIA	PCMCIA 2.0 interface; two Type I/II cards or one Type III card; Hot Swap
Input/Output	ISDN, Ethernet, SCSI-2, parallel, two serial ports, external keyboard/mouse, modem, 16-bit stereo audio (stereo headphone output, stereo line output, stereo line input)
Ethernet	IEEE 802.3-compliant, 26-pin high density mini-D, AUI available via adapter cable
Parallel	Centronics-compatible parallel port, 26-pin high density mini-D
Serial	Two Sun-compatible 38.4 Kbaud RS-232 async/sync serial ports with 8-pin mini-DIN
SCSI	Fast (10MB/sec) SCSI-2 (synchronous), 50-pin mini-D SCSI connector
Audio	16-bit, mini-DIN
Battery Options	Internal: removable, rechargeable 12V 1.8AH NiMH; 1.5 hours typical operating time with power management; weight: 0.9 lb External: rechargeable 12V 5.5AH NiCd; 5 hours typical operating time with power management; weight 4 lbs
Power Supply/Charger	Universal input: 110-240V AC; Output: 12V DC, 0-4.6A DC
Case	Magnesium alloy metal case
Approvals	FCC Class B; CE Mark; UL

Dimensions 11.8" x 8.5" x 2.0" (300 x 216 x 51 mm)

Weight 7.0 lb including battery

(*Call [your local office](#) or 1-800-966-RAVE for Exceptional Pricing!*)

[HOMEPAGE](#) [↑](#) [CONTACT W/ RAVE](#) [WHAT'S NEW](#) [ORDERING](#) [WEBMASTER](#) [SEARCH our SITE](#)

Copyright © 1997 RAVE Computer Association, Inc. All rights Reserved.