

T4800CT

General Information

Model number: T4800CT TFT Color display 500MB PA1161U-T2A (FCC ID# CJ6UK454)

Dimensions: T4800CT - 11.7"W x 8.3"D x 2.2"H

Weight: 6.9lbs. with battery pack

Voltage: Computer DC input: 18VDC, 1.7A
Universal AC adapter: 100-240 VAC 50-60 Hz

Batteries: Removable rechargeable NiMH battery pack
2 + hrs. battery life per charge; recharges in 1.5 hrs. off/3 hrs. on
Internal NiMH backup battery for memory backup, vanadium lithium RTC battery for real time clock

CPU: SL enhanced IntelDX4™ DX4 75MHz (3.3 volt with 16KB internal cache; integrated math coprocessor)

RAM memory: 8MB standard, 3.3 volt operation (640KB conventional memory plus 7.25MB which can be configured as RAM disk, expanded (LIM/EMS 4.0), and/or extended memory, plus 128KB shadow ROM
Memory expandable up to 24MB using 4, 8, or 16MB
3.3 volt user installable credit card style memory

Video: 1MB video RAM
Local-bus video and graphics accelerator with BitBLT WD90C24A or WD90C24A2

Number of keys: 82

Keyboard type: 101-key keyboard compatible. Full function 82 key sculptured
dedicated cursor
keyboard with 12 dedicated function keys and 8 control keys. Arrow keys arranged in an inverted "T" pattern.

Drives: One 1.44MB 3.5" floppy disk drive; one 500MB hard disk drive

Standard features: MaxTime™ power management capabilities including:
AutoResume safety data protection
Resume electronic bookmark
Selectable processing speeds
CPU sleep mode
Automatic display and hard drive power down
Low battery warning and audible alarm
System auto off
LCD Brightness
Battery save mode
Speaker volume
Software sounds
Panel power
Card modem power
Auto on timer
Panel close alarm
Digital/Analog battery gauge
HWSetup™ System Configuration including:
Memory information
HDD information
PCMCIA slot/Serial port/Parallel port setup
Display setup

CPU cache enable
Hotkey enable
Boot Priority configuration
Sound system address configuration
Sound system power on/off
Ext. keyboard Fn key configuration
APM integrated in system BIOS
QuickRead status icons
System control hotkeys including instant hotkey
screen blank
BIOS in Flash ROM
Multi-level password protection
Shadow BIOS ROM
System reset button
3 year U.S. and International warranty (One year
warranty on battery)
Product Support
Meets standards for EPA Energy Star Computer Program
Preinstalled software: MS-DOS(R) 6.21 operating system
Windows For Workgroups 3.11
Windows Sound System 2.1
Run Time Video for Windows 1.1
Indeo™ Video 3.1
UltraFont(TM) or Stretch
Toshiba Card Manager 3.0
MaxTime(R) utility for Windows 3.11
QuickPort(TM) drivers
Hypertext on-line documentation (disk resident)
includes T4800CT reference manual
Pointing device: BallPoint(R) mouse version 2.0 with cordless
QuickPort™ connection

Software Compatibility:

Compatible with software written for the IBM(R) PC/XT/AT using VGA(R),
EGA,
or CGA resolution graphics modes.
IBM(R) super video graphics array (SVGA) compatible display system.
Microsoft Windows Sound System (wave audio) compatible.

Interfaces

SVGA color video port (supports 640 x 480, 256 colors
internal or external; 800 x 600, 16 colors; 800 x 600,
256 colors; 1024 x 768, 256 colors external)
PCMCIA 2.01 compliant slot (16mm) supports type I, II, or III cards
PCMCIA 2.01 compliant slot (5mm) supports type I or II cards
RS-232-C serial port
Parallel printer/external diskette drive port
150 pin expansion bus connector for optional Desk Station
IV docking station or optional SCSI adapter
PS/2 keyboard port
PS/2 mouse port
Credit card style memory slot
Kensington(R) cable lock slot
QuickPort™ connection for BallPoint(R) mouse
Audio-out headphone or external speaker jack
Input jack for external microphone

Audio System

16 bit sound
Wave audio compatibility
Built-in stereo speaker and microphone
Headphone or external speaker jack
Microphone jack

Color TFT-LCD Active Matrix Display

Display area: 7.6"W x 5.7"H; 9.5" diagonal
Resolution: 640 x 480
Dot pitch: .30mm(W) x .30mm(H)
Aspect ratio: 1 : 1
Contrast: 100 : 1 Max; 60:1 Min.
Colors: 256 colors out of a palette of 262,144 in 640 x 480 mode
Simultaneous display to external monitor on video modes up to 640 x 480, 256 colors

2.5" 500MB Hard Disk Drive

Toshiba HDD: MK2428FC
Interface: IDE
Average access time: 12ms
Recording method: RLL 1-7

Hardware Switches and Controls

- 1) Power on/off
Located on left side of computer
- 2) Reset
Located on left side of computer

Environmental Specifications

- 1) Operating condition
 - Ambient temperature: 41 to 95 degrees F.
5 to 35 degrees C.
 - Relative humidity: 20% to 80% (non-condensing)
 - Altitude (from sea level): -60 to 3,000 meters
- 2) Non-Operating condition
 - Ambient temperature: -4 to 149 degrees F.
-20 to 65 degrees C.
 - Relative humidity: 10% to 90% non-condensing
 - Altitude (from sea level): 30,000 ft.
- 3) Wet bulb temperature condition
 - Ambient temperature: 79 degrees F / 26 degrees C maximum

HotKeys used with Fn key

Fn + F1 Instant security ON/OFF
Fn + F2 Power save mode
Fn + F3 AutoResume Enable/Disable
Fn + F4 Speaker volume adjustment - off, high,

Fn + F5	medium, low - press key repeatedly to set level Internal/Simultaneous/External displays - press key repeatedly to set choice
Fn + F10	Toggles keypad overlay
Fn + F11	Toggles num lock
Fn + F12	Toggles scroll Lock
Fn + Up/Down arrow	Brightness adjustment
Fn + Alt	Simulate IBM(R) enhanced keyboard Right ALT
Fn + Ctrl	Simulate IBM(R) enhanced keyboard Right CTRL
Fn + Enter	Simulate IBM(R) enhanced keyboard numeric keypad

enter

Options and Extra Accessories

PC-PA2012U	4MB 3.3V memory card
PC-PA2013U	8MB 3.3V memory card
PC-PA2014U	16MB 3.3V memory card (no longer manufactured)
T24NW	Noteworthy(TM) PCMCIA Type II 2400/9600bps data/fax modem (no longer manufactured)
T144NWX	Noteworthy(TM) 14,400 bps data/fax modem, PCMCIA Type II (no longer manufactured)
PC-T144PF4	14mm 14,400 bps data/fax modem (dual RJ-11), PCMCIA compliant (no longer manufactured)
NW144CR	Noteworthy(TM) 14,400 bps Cellular-Ready data/fax modem, PCMCIA Type II
NWTR01X	Noteworthy(TM) PCMCIA type II Token Ring card
NWETH01X	Noteworthy(TM) 10BaseT PCMCIA type II Ethernet card
NWETH02X	Noteworthy(TM) 10Base2 PCMCIA type II Ethernet card
NW3270	Noteworthy(TM) PCMCIA type II 3270 emulation card
SW3270	IBM(R) PC/3270 software for NW3270 card
NWHD105M3	Noteworthy(TM) 105MB Hard disk drive, PCMCIA Type III
NWHD262M3	Noteworthy(TM) 262MB hard disk drive PCMCIA Type III
PA28064	Cryptcard PCMCIA Type II (DES) data encryption card
PA2429URA	Battery pack, NiMH (2600mAh)
PC-PA2422U	Battery pack recharger with AC adapter
PC-PA2478U	Universal AC adapter
PC-PA801L	Statpower auto adapter (requires universal AC adapter)
PC-PA2113	Toshiba 150 pin SCSI adapter (no longer manufactured)
PC-PA3350L	Kensington(R) security cable lock
PC-PA2701U	Deskstation IV
PC-PA180B	PC pack carrying case (blue)
NWCCDFB	Universal fabric carrying case
NWCCAFB	Twin fabric carrying case
NWCCALB	Twin Executive leather carrying case, black
NWCCBLB	Leather expanded size carrying case
PC-PA1050L	Leather attach, case
PA2209US	External PS/2 keyboard
PA2805U	BallPoint(R) mouse V2.0 with Quickport connection
NW500L	Noteworthy(TM) NewsCard(TM) wireless receiver, PCMCIA Type II
NW621P	17-key numeric keypad with pass through parallel interface
NW623S	17-key numeric keypad with serial interface
NWMOTO	Cellular direct connect cable kit (Motorola)
NWNOKI	Cellular direct connect cable kit (Nokia)